



## **S-Series**

Suspension & Windshield Kit



**XLR CABLE INCLUDED**

## S-SERIES

This latest design incorporates a new suspension concept, new materials and new windshield construction for refined performance and ease of use.

Lightweight with a minimum of parts and tough enough to withstand the rigours of ENG, the S-SERIES is ready to use straight out of the box.

The S-SERIES retains all the flexibility, balance and professional performance that you can expect from a Rycote system.



 Rycote



### S-SERIES SUSPENSION

- One-piece web suspension elements - no rubbers or elastics
- Patented design gives ideal isolation for all axial microphones
- Unaffected by temperature and all-but unbreakable
- Suitable for microphones 19mm (¾") to 25mm (1") in shaft diameter
- Snap-in webs with six positions for perfect balance and fit
- Matched, high-flexibility microphone cable with twin clamps
- Pinch-release fittings for webs and cable clamps for quick and easy repositioning

**XLR CABLE INCLUDED**

### CABLE/CONNECTORS SPECIFICATION

- Balanced microphone twin with ultra-fine stranded copper cores (18 x 0.1mm) and a helical screen
- 3mm soft PVC jacket for high flexibility even at low temperatures
- Neutrik NC3 (XLR-style) connectors with gold-finished pins

**STRUCTURE**

- Steel spine for core strength and rigidity
- Central chassis ring secures windshield pods and allows fast access to the microphone
- Chassis ring can be demounted when only a suspension is required

All S-series systems are supplied with our **NEW pistol grip handle.**





**S-SERIES WINDSHIELD**  
(windscreen)

- The windshield (windscreen) uses pairs of "Pods" which twist-lock to the chassis ring
- All pods are 100mm (4") diameter but come in four different lengths (see sizes below)
- Four kit sizes combine the pods to house microphones from <200mm (8") to a maximum of 410mm (16")
- The acoustic fur covering (30mm staple) is integral and can give >30dB windnoise suppression (100-500Hz)



**POD SIZES**

<b>Pod U125</b>	Tube length	125mm (5")
<b>Pod U150</b>	Tube length	150mm (6")
<b>Pod U180</b>	Tube length	180mm (7")
<b>Pod U225</b>	Tube length	225mm (9")

**SYSTEM KIT SIZES**

S-SERIES Kit	Order Code	Overall Body Length	Front Pod	Rear Pod
<b>S-SERIES 300 Kit</b>	010301	305 mm (12")	U180 180mm (7")	U125 125mm (5")
<b>S-SERIES 330 Kit</b>	010302	330 mm (13")	U180 180mm (7")	U150 150mm (6")
<b>S-SERIES 375 Kit</b>	010303	375 mm (15")	U225 225mm (9")	U150 150mm (6")
<b>S-SERIES 450 Kit</b>	010304	450 mm (18")	U225 225mm (9")	U225 225mm (9")

**GENERAL GUIDE FOR LENGTH**

For microphone lengths (excluding XLR)

<b>S-SERIES 300 kit</b>	200mm (8") OR LESS	- 255mm (10")
<b>S-SERIES 330 kit</b>	260mm (10")	- 280mm (11")
<b>S-SERIES 375 kit</b>	285mm (11")	- 325mm (13")
<b>S-SERIES 450 kit</b>	355mm (14")	- 410mm (16")



**NEW** pistol grip handle  
supplied with all S-SERIES system kits



Rycote is a family owned and run company and has been manufacturing microphone shock mounts and windshields for over forty years.

We are very proud to say that we design, develop and manufacture all our products at our factory in Stroud, U.K.

**Rycote Microphone Windshields Ltd**

Libby's Drive, Slad Road  
Stroud  
Glos, GL5 1RN  
United Kingdom

**Tel** + 44 (0) 1453 759338

**Fax** + 44 (0) 1453 764249

**Email** [info@rycote.com](mailto:info@rycote.com)

**[www.rycote.com](http://www.rycote.com)**



Rycote brochures are printed on recycled paper.

